



MATERIAL SAFETY DATA SHEET

Name of Material Oil Spot Primer	
1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
E	PROTECTIVE EQUIPMENT

OSHA 174: May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard

must be consulted for specific requirements.

US Department of Labor: Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Section I - PRODUCT IDENTIFICATION

PRODUCT NAME: Latex-ite® Oil Spot Primer
MANUFACTURER NAME: Dalton Enterprises, Inc.
ADDRESS: 131 Willow Street Cheshire, CT 06410
EMERGENCY PHONE NUMBER: (203) 272-3221
AFTER 5 PM AND ON WEEKENDS: (203) 272-3221
ORIGINATOR: WM
CHEMICAL FAMILY: Mixture
EFFECTIVE DATE: 01/15/10
DATE SUPERSEDED: 01/06/06

Section II - CHEMICAL IDENTITY INFORMATION

Acrylic Polymer

CAS #: Proprietary
Listed in SARA Title III, Section 313: No
OSHA PEL: N/A
ACGIH TLV: N/A
STEL: N/A
LC50: N/A
LD50 N/A

Water

CAS #: 7732-18-5
Listed in SARA Title III, Section 313: No

Section III - PHYSICAL / CHEMICAL CHARACTERISTICS

APPEARANCE & ODOR: Milky appearance, slight acrylic odor
BOILING POINT: 212⁰F
VAPOR PRESSURE: Nearly equal to water.
SPECIFIC GRAVITY: 1.02
SOLUBILITY IN WATER: Infinite
VAPOR DENSITY (Air = 1): <1
PHYSICAL STATE: Liquid
FREEZING POINT: 32⁰F
VOC: 0 g/L

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLAMABILITY CLASSIFICATION: N/A **FLAMMABLE LIMITS:** N/A
LOWER EXPLOSIVE LIMIT (LEL): N/A
UPPER EXPLOSIVE LIMIT (UEL): N/A
EXTINGUISHING MEDIA: Water, foam and dry chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear self-contained breathing equipment in addition to normal personal protective equipment. Do not allow run off from fire fighting procedures to enter public waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A.

Section V – HEALTH HAZARD DATA

Route(s) of Entry: Inhalation? Yes Skin Contact? No Ingestion? Yes Eye Contact? Yes

Health Hazards (Acute and Chronic):

(Acute): Dizziness, weakness, nausea, headache.

(Chronic): Gastrointestinal irritation – repeated or prolonged exposure to high vapor concentrations may cause damage to liver, kidneys, lungs, blood, or central nervous system. Repeated ingestion may cause liver damage.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Signs and Symptoms of Exposure:

Inhalation: Vapor could cause headache, irritation to nose and throat, dizziness, weakness and nausea.

Ingestion: Can cause nausea, vomiting and diarrhea.

Skin: Not easily absorbed – repeated or prolonged exposure may be mildly irritating to skin. May cause allergic reactions to skin in some people.

Eye: Irritation from vapor or liquid.

Medical Conditions Generally Aggravated by Exposure: None known.

Emergency and First Aid Procedures:

Inhalation: Remove / relocate to fresh air and provide oxygen if breathing is difficult. If not breathing, give artificial resuscitation. IMMEDIATELY CALL A PHYSICIAN.

Ingestion: If vomiting begins keep head below hips to avoid aspiration into lungs. DO NOT INDUCE VOMITING. Give victim a glass of water or milk. Never give anything via mouth to an unconscious person. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

Skin contact: Wash area with soap and water. Remove contaminated clothing. IF IRRITATION OCCURS, CALL A PHYSICIAN.

Eye Contact: Gently flush with large amounts of water for at least fifteen minutes or until eye is clear. IMMEDIATELY CALL A PHYSICIAN.

Section VI – REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Keep from freezing and extreme heat.

INCOMPATIBILITY (materials to avoid): Strong oxidizers.

HAZARDOUS POLYMERIZATION: Will Not Occur.

HAZARDOUS DECOMPOSITION or BYPRODUCTS: Combustion may yield fumes, smoke, carbon monoxide, carbon dioxide and other toxic pyrolysis products.

CONDITIONS TO AVOID: High temperatures. Keep product from freezing.

Section VII – SAFE HANDLING PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike and contain spill with inert material (sand, sawdust, etc). Pump liquid into storage tanks. Place in closed container for proper disposal.

WASTE DISPOSAL METHOD: Dispose in accordance with federal, state and local regulations.

PRECAUTIONS IN HANDLING/STORAGE: Keep container closed and upright to prevent leakage. Avoid freezing or temperatures above 50 degrees Celsius.

OTHER PRECAUTIONS: Do not take internally. Keep away from children. Avoid breathing vapors. For external use only.

Section VIII – CONTROL MEASURES

VENTILATION: Local Exhaust: Yes Mechanical (general): N/A Special: N/A Other: N/A

RESPIRATORY PROTECTION: None required if good ventilation is maintained. Otherwise use NIOSH approved respirator designed to remove particles and vapor.

PROTECTIVE GLOVES: Yes.

EYE PROTECTION: Yes.

OTHER PROTECTIVE EQUIPMENT: Rubber apron is recommended to protect clothing from splash during application.

OTHER: Do not apply during or just before (within one hour) of rain to avoid contamination of runoff water. Wash hands prior to eating.

Section VIX – DISCLAIMER

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.