



MATERIAL SAFETY DATA SHEET

Name of Material Asphalastic Crack Filler	
1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
<input type="checkbox"/>	PROTECTIVE EQUIPMENT

Section I - PRODUCT IDENTIFICATION

PRODUCT NAME: Latexite[®] Asphalastic Crack Filler
MANUFACTURER NAME: Dalton Enterprises, Inc.
ADDRESS: 131 Willow Street Cheshire, CT 06410
EMERGENCY PHONE NUMBER: (203) 272-3221
AFTER 5 PM AND ON WEEKENDS: (203) 272-3221
ORIGINATOR: K.P.
TRADE NAMES & SYNONYMS: Asphalt Patch Materials
CHEMICAL FAMILY:
EFFECTIVE DATE: 02/25/2008
DATE SUPERSEDED: 03/01/2007

Section II - HAZARDOUS / NON-HAZARDOUS INGREDIENTS

Asphalt/Asfalto:

CAS #8052-42-4
Listed in SARA Title III, Section 313: NO
OSHA PEL: 10ppm
ACGIH TLV: 5 mg/m³ (volatiles)
LC50: Human >0.3ppm
LD50: N/A

Clay/Arcilla:

CAS #1332-58-7
Listed in SARA Title III, Section 313: No
OSHA PEL: 5 mg/m³ (dust)
ACGIH TLV: 2 mg/m³ (dust)
STEL: N/A
LC50: N/A
LD50: N/A

Water/Agua:

CAS #7732-18-5

N/A = Not available or applicable

Ingredients total weight % are below 100% only if all others unlisted are not considered hazardous by any federal (OSHA, WHMIS, SARA), any state or province, or local Right-To-Know regulations.

Section III - PHYSICAL DATA

APPEARANCE & ODOR: Black Liquid, Asphaltic Oder
BOILING POINT: N/A
VAPOR PRESSURE: N/A
SPECIFIC GRAVITY: N/A
SOLUBILITY IN WATER: Dispersed in water, insoluble when dry.
EVAPORATION RATE: Not Known
PH:
PHYSICAL STATE: Liquid
FREEZING POINT: 32° F
%VOLATILE (by Wt.):
VAPOR DENSITY: 1
THRESHOLD ODOR: N/A
WATER/OIL DIST. COEFFIECIENT: N/A
MAX VOC: Less than 10 g/L

Section IV – FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: N/R
Flash Point (method used): Greater than 210 degrees F. TCC
Flammable Limits: LEL: N/A **UEL:** N/A
Combustion Products: Hydrocarbon compounds, CO, and CO₂.
Extinguishing Media: Water, Foam, dry chemical, CO₂.
Special Fire Fighting Procedures: Cool exposed containers to prevent steam pressure buildup. Wear self-contained breathing equipment.
Unusual Fire and Explosion Hazards: Closed containers may build up pressure from heat. Dust residues can potentially form explosive mixtures with the air. Use adequate ventilation with clean-up procedures. Burning liquid can float on water and spread further.
UN/NA/PIN#: N/A
NFPA Rating: **Health 1;** **Fire 1;** **Reactivity 0**
Impact Sensitive: No
Static Sensitive: No
Explosive Power: N/A
Burning Rate: N/A

Section V – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II
ROUTES OF ENTRY: Skin, eyes, inhalation, ingestion.
EFFECTS OF OVEREXPOSURE / ACUTE OVEREXPOSURE:
Eyes: May cause severe eye irritation which can result in irreversible damage.
Inhalation: May cause headaches, dizziness, nausea vomiting and perhaps loss of consciousness. Vapors may be irritating to eyes, nose and throat.
Skin: May cause irritation of skin and/or systemic effects by absorption.
Ingestion: May result in vomiting; aspiration of vomitus must be avoided as liquid contact with the lungs can result in chemical pneumonitis and pulmonary edema/hemorrhage. Have patient drink large amounts of water; contact a physician.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

Section VI - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Keep from freezing.

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition Products: N/A

Hazardous Polymerization: Will not occur.

Conditions to Avoid: High temperatures. Keep product from freezing.

Section VII - SPILL OR LEAK PROCEDURES

SARA TITLE III:

#302: No #304 CERCLA: No #313: No RCRA: No

Steps to be taken in case material is released or spilled:

Ventilate the area. Wear suitable protective clothing, gloves and eye/face protection. Contain and pick up waste materials. Put in a sealed, approved container. Dispose of in accordance with federal, state and local regulations.

Reportable Quantity (lb.): N/A

TPO (lb.): N/A

Regulations: WHMIS, SARA, state and province.

Hazardous Waste: N/A

Section VIII - SAFE HANDLING AND PROTECTION INFORMATION

Respiratory Protection: Use only with adequate ventilation. If ventilation is inadequate, wear approved respiratory equipment.

Ventilation:

Local Exhaust: Required

Mechanical (general): Required

Special: N/A

Other: N/A

Protective Gloves: Rubber gloves

Eye Protection: Wear safety glasses, goggles or face shield.

Other Protective Equipment: Wear suitable protective clothing.

Estimated LD50, MG/KG: N/A

Estimated LC50, MG/KG: N/A

Sensitization: N/A

Irritant: Yes

Section IX – SPECIAL PRECAUTIONS

Keep out of reach of children.

For professional and industrial use only.

Always read label plus precautions and follow directions carefully.

Keep from freezing.

Do not breathe vapor or spray mist.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Additional Technical Data Sheets and/or MSDS are available upon request.

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.