



MATERIAL SAFETY DATA SHEET

| Name of Material | |
|------------------|----------------------|
| Crack Tube | |
| 2 | HEALTH |
| 1 | FLAMMABILITY |
| 0 | REACTIVITY |
| J | PROTECTIVE EQUIPMENT |

Section I - PRODUCT IDENTIFICATION

PRODUCT NAME: Latexite[®] Crack Tube
MANUFACTURER NAME: Dalton Enterprises, Inc.
ADDRESS: 131 Willow Street Cheshire, CT 06410
EMERGENCY PHONE NUMBER: (203) 272-3221
AFTER 5 PM AND ON WEEKENDS: (203) 272-3221
ORIGINATOR: K.P
EFFECTIVE DATE: 02/25/2008
DATE SUPERSEDED: 01/10/2006

Section II - HAZARDOUS / NON-HAZARDOUS INGREDIENTS

Hazardous Components (chemical & common names)
Cut Back Petroleum Asphalt CAS# 8052-42-4
Mineral Spirits - Gilisonite
Limestone+ Fillers

N/A = Not available or applicable

Ingredients total weight % are below 100% only if all others unlisted are not considered hazardous by any federal (OSHA, WHMIS, SARA), any state or province, or local Right-To-Know regulations.

Section III - PHYSICAL DATA

| | |
|-------------------------------------|--|
| BOILING POINT: 315° - 380° F | SPECIFIC GRAVITY (H2O=1): 1.10 |
| VAPOR PRESSURE (mm Hg): N/A | PERCENT VOLATILE |
| VAPOR DENSITY (Air): N/A | BY VOLUME %): 30 |
| SOLUBILITY IN WATER: N/A | EVAPORATION RATE (Water =1): 0.1 |
| | APPEARANCE AND ODOR: Black Mastic Asphalt Solvent |
| | MAX VOS/VOC: 5 g/L |

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 110° F T CC Combustible
Flammable Limits in Air % by Volume:
EXTINGUISHER MEDIA: CO₂ Dry Chemical
SPECIAL FIRE FIGHTING PROCEDURES: Treat as fuel fire
UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

Section V - HEALTH HAZARD DATA

STABILITY: Stable
CONDITIONS TO AVOID: Keep away from heat, sparks and open flame.
INCOMPATIBILITY (Materials to avoid): Water and Oxidizing materials.
HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID:

Section VI - REACTIVITY DATA

THRESHOLD LIMIT VALUE EFFECTS OF OVEREXPOSURE:

ACUTE OVEREXPOSURE: N/A

CHRONIC OVEREXPOSURE: N/A

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Asphalt fume mineral spirits.

EYES: N/A

SKIN: Prolonged or repeated skin contact may cause mild irritation.

INGESTION: N/A

Section VII - SPILL OR LEAK PROCEDURES

SARA TITLE III:

#302: No #304 CERCLA: No #313: No RCRA: No

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep away from heat, sparks and open flame. Dike spills with sand bags or earth.

WASTE DISPOSAL METHODS (Consult federal, state, and local regulations): Follow all federal, state and local regulations.

Reportable Quantity (lb.): N/A

TPO (lb.): N/A

Regulations: WHMIS, SARA, state and province.

Hazardous Waste: N/A

Section VIII - SAFE HANDLING AND PROTECTION INFORMATION

Respiratory Protection:

Ventilation:

Local Exhaust: Required

Mechanical (general): N/A

Special: N/A

Other: N/A

Protective Gloves: Rubber gloves

Eye Protection: Wear safety glasses, goggles or face shield.

Other Protective Equipment: Long Sleeve shirt and long trousers.

Section IX - SPECIAL PRECAUTIONS

Keep out of reach of children.

For professional and industrial use only.

Always read label plus precautions and follow directions carefully.

Keep from freezing.

Do not breathe vapor or spray mist.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Additional Technical Data Sheets and/or MSDS are available upon request.

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.